

# HR-221



## Vantager

### Palm Size/ Hi-Speed/ Adapter-less

### Multi Card Reader/ Writer

#### Key Features:

- Stand-alone/ palm size / high-speed/ adapter-less media storage card reader.
- USB (Universal Serial Bus) 2.0 specification interface.
- Compliant with USB Mass Storage device class specification.
- Supports RS MMC 4.0 8-Bit specification.
- Supports new xD v1.2 specification.
- Five slots can accept up to 25 types of media card.
- Supports small form factor flash card; such as mini SD, RS-MMC, T-flash, MS-Duo etc.
- Hot swappable and Plug & Play capability.
- Slots can be used at the same time for data exchange except T-flash and SD slots.
- Supports Media Card-Icon display.
- Supports two icon-indicators for easy recognition.
- Work on Bus-powered, no external power supply required.

#### Specifications:

Five Memory Slots:	CF/MD, SM/xD , SD/mini SD/MMC , MS/MS-Duo , T-Flash
Four Media Icons display:	MMC/SD/(T-Flash), Compact Flash I/II, Smart Media/xD, MS/MS Pro
Media card supports:	CF (TypeI & TypeII) , CF Ultra II, Micro Drive, Magic Gate , SM, SM ROM, xD, XD M-series , SD, SD Ultra II, mini SD, MMC-I, MMC-II, MMC 4.0,MMC Dual Voltage, RS-MMC, RS-MMC Dual Voltage, RS-MMC 4.0, T-Flash, MS, MS Select, MS ROM, MS PRO, MS Magic Gate, MS-PRO Magic Gate, MS-DUO Magic Gate, MS-PRO-DUO etc.
Indicators:	<ul style="list-style-type: none"><li>● One power-on icon indicator.</li><li>● One media R/W icon indicator.</li></ul>
Interface:	5-Pin Mini USB support USB1.1/2.0
Operating temperature:	0°C~40 °C
Stock temperature:	-20°C~60°C
Board Dimensions (L*D):	65*55mm
Housing Dimensions (L*D*H):	73*59*17 mm
Certification:	FCC Class B, CE
System support:	<ol style="list-style-type: none"><li>1. Windows® 98/SE, Windows®ME, Windows®2000, Windows®XP, VISTA</li><li>2. Mac OS 8.6X or higher</li><li>3. Linux OS 2.4.X or higher</li></ol>

### **Package contents:**

- Card Reader
- One USB cable
- Setup disc with electronic manual

### **Ordering Information:**

**HR-221 Multi Card Reader/Writer**



**HEISEI** Electronics Co. Ltd

Tel: 886-29152150 Fax: 886-29152849

<http://www.heisei.com.tw> E-mail: info@heisei.com.tw