

# SOHOUSB

It's simple, easy and faster!!



## Vive

### Palm Size/ Hi-Speed/ Adapter-less

### 32 in 1 External Card Reader / Writer

#### Key Features:

- Stand-alone/ palm size / high-speed/ adapter-less media storage card reader.
- USB (Universal Serial Bus) 2.0 specification interface.
- Compliant with USB Mass Storage device class specification.
- Supports RS MMC 4.0 8-Bit specification.
- Supports new xD v1.2 specification.
- Five slots can accept up to 32 types of media card.
- Supports small form factor memory card; such as mini SD, RS-MMC, Micro SD, MS-Duo etc.
- Hot swappable and Plug & Play capability.
- Slots can be used at the same time for data exchange except Micro SD and SD slots.
- Supports Icon display for media cards.
- Supports two indicators for easy recognition.
- Work on Bus-powered, no external power supply required.

#### Specifications:

Five Memory Slots:	CF/MD, SM/xD , SD/mini SD/MMC , MS/MS-Duo , Micro SD
Four Media Icons display:	MMC/SD, Micro SD, Compact Flash I/II, Smart Media/xD, MS/MS Pro
Media card supports:	CF (TypeI & TypeII) , CF Ultra I & II, Micro Drive, SM, SM ROM, xD, M-series xD, SD, SD Ultra II, mini SD, MMC-I, MMC-II, MMC 4.0,MMC Dual Voltage, RS-MMC, RS-MMC Dual Voltage, RS-MMC 4.0, Micro SD, MS, MS Select, MS ROM, MS Magic Gate, MS-PRO Magic Gate, MS-DUO Magic Gate, MS-PRO-DUO Magic Gate etc.
Indicators:	<ul style="list-style-type: none"><li>● One power-on icon indicator.</li><li>● One media R/W icon indicator.</li></ul>
Interface:	5-Pin Mini USB support USB1.1/2.0
Operating temperature:	0°C~40 °C
Stock temperature:	-20°C~60°C
Board Dimensions (L*D):	65*55mm
Housing Dimensions (L*D*H):	73*59*17 mm
Certification:	FCC Class B / CE
System support:	<ol style="list-style-type: none"><li>1. Windows®2000, Windows®XP /VISTA</li><li>2. Mac OS 8.6X or higher</li><li>3. Linux OS 2.4.X or higher</li></ol>

#### Package contents:

- Card Reader
- One USB cable
- Setup disc with electronic manual

#### Ordering Information:

**HR-222AL 32 in 1 External Card Reader / Writer**

 **HEISEI** Electronics Co. Ltd

Tel: 886-29152150 Fax: 886-29152849

<http://www.heisei.com.tw> E-mail: info@heisei.com.tw