



Key Features:

- Provide bus master function with OHCI interface specification
- IEEE 1394-1995 compliant and compatible with Proposal 1394a
- Supports serial bus data transfer rates of 100, 200 and 400Mbps
- Max 63 computer and consumer device connection
- Real plug and play and hot swappable capability
- Easy to add three high-speed FireWire ports to desktop
- Latest PCI specification, PCI 2.1 & PCI power management compliant
- Support Peer-to-Peer data repeater function
- Over current protection by each port
- Low profile design; support low profile and standard bracket

Specifications:

Chipset:	Agere (Lucent)
Topology:	Both tree and bus topology supported
Connector:	Three IEEE-1394 root ports
Transfer rate:	100, 200 and 400Mbps.
Operating temperature:	5°C~40 °C
Stock temperature:	-20°C~60°C
Humidity:	0%~80% RH, non-condensing
Board Dimensions:	120*73 mm
Emission:	FCC Class B, CE

Applications:

AV Applications: D8 、 PC Camera 、 DV Camcorder 、 DV Recorder 、 Digital TV
Storage Devices: High speed hard disk 、 CD-ROM 、 DVD ROM
Other: Scanner 、 Printer

System Requirements:

- PC and Mac system with one free PCI slot
- Windows 98SE 、 2000 、 ME 、 XP and Mac OS. 8.6 or higher

Ordering Information:

HF-1394LB 3 Port 1394 PCI Host Adapter

