



HBU-330NC *2 Ports USB 3.0 Express Card*

- Compliant to USB 3.0 specification revision 1.0
- Compliant to Intel xHCI specification revision 0.96
- Compliant with ExpressCard specification 1.0
- Supports SuperSpeed data transfer rate up to 5.0Gbps
- 2 USB ports to support SuperSpeed/ High-Speed/ Full-Speed/ Low-Speed
- More power at the connector, max. 900mA
- Actual Bus Power: 600mA combined for two ports
- Built-in DC jack for receiving extra power supply
- Supports ExpressCard/34mm slot
- Supports hot swapping capability to plug and unplug the devices without shutting down the system

Features

Electronic Specification

Max. Data Transfer Rate	5.0Gbps
System Interface	ExpressCard/34mm
External Port	2 USB ports (Supports SuperSpeed/ High-Speed/ Full-Speed/Low-Speed)
Power Input	DC +5V (Extra power adapter connector Ø1.3mm)
Output Voltage Per Port	DC +5V
Output Current	Max. 900mA each port with AC power adapter Max. 600mA combined for two ports via bus power
Operating Temperature	0°C~40 °C
Certification	FCC Class B, CE
System support	Windows XP, Windows Vista, Windows 7 (32/64-bit)

Mechanical Specification

Dimensions (L*W*T)	116.6*34*5 mm
Weight	30g