



Mini IPC

System		
CPU	Onboard Intel Celeron M 1.0GHz (FSB 400MHz)	
Memory	1 x 200 Pin DDR SODIMM up to 1GB DDR 200/266	
Chipset	Intel 852GM + ICH4	
Graphics	- 852GM Integrated VGA/LCD Controller, 2D/3D GUI engine, Sharing memory architecture up to 64 MB - Support Dual Display	
Network	Intel® 82562ET 10/100 LAN Base-T fast Ethernet	
Audio	Onboard AC'97 Audio Codec	
Power Supply	DC +12V power input	
Display		
LCD	6.5"	8.4"
Max. Resolution	640 x480	800 x 600
Brightness	400 nit	220 nits
Touch Screen	DMC	DMC
Storage		
HDD	N/A	
CF	1 x Compact Flash type I/II socket support up to 4GB	
I/O Ports		
USB	3 x USB 2.0 (Rear) : 1 x onboard	
Serial Ports	1 x RS232 (Rear) : 1 x onboard	
LAN	1 x RJ-45 interface	
PS/2	1 x PS/2 port (with Y split cable For keyboard and mouse)	
Audio	1 x Mic in / 1 x Line-out	
VGA	1 x DB-15 VGA interface for 2 nd display	
Physical Dimensions		
	6.5"	8.4"
Dimensions/ Weight	243(W)x166(H) x 70(D) mm	243(W)x201(H) x 67(D) mm
	2Kg	2.2Kg
Environment		
EMC & Safety	CE, FCC	
Temperature	Operating: 0 ~ 40°C Storage: -20 ~ 60°C	
Humidity	10% ~ 90%	
Optional Items		
OS	Windows XP/2K/XPE/WinCE	

* The specification is subject to change without any prior notice.

 **HEISEI** Electronics Co., Ltd.

3F, NO. 5, Alley 8, Lane 45, Pao Hsin RD.,
Hsin-Tien City, Taipei Hsien, Taiwan R.O.C.

Tel: 886-2-2915-2150 Fax: 886-2-2915-2157

http://www.heisei.com.tw/ E-mail: info@hei-sei.com