

# WP-800 Line Thermal Printer

## Station thermal printer Features:

Smallest size among others.  
 High-speed printing.  
 The resident data buffer has storage capacity of 8K bytes.  
 Esc/pos command compatible.  
 Provides variety of interface.  
 Paper end and near end sensor, head up sensor.  
 Repeat previous Button(option)  
**Two Drawer Kick Out.**  
 Barcode and Bitmap printing capability



## General Specifications:

<b>Power supply</b>	DC24V		<b>Fast feed speed</b>	150 mm/second	
<b>Printer method</b>	Thermal line		<b>Paper width</b>	83 mm	
<b>SRAM</b>	128K		<b>Weight</b>	1.8 kg	
<b>Flash</b>	512 KB		<b>MTBF</b>	50 x 10 <sup>6</sup> million lines Changing Rate of Average head resistance:+/- 15% or less	
<b>Print Speed</b>	150 mm/s		<b>Detect Sensor</b>	Paper end and near end sensor.	
<b>Character structure</b>	Alphanumeric	95	<b>Interface</b>	Optional RS-232C, Centronics, RS-485, USB, 10 Base-T	
	International	37 128 x 8 Graphic		<b>Environmental condition:</b>	
<b>Number of columns</b>	56/42 columns			<b>Temperature</b>	<b>Humidity</b>
<b>External dimensions (W) x (D) x (H)</b>	140.7x 190 x 137 mm		<b>Operating</b>	5~ 40	30% ~ 85%
			<b>Storage</b>	-20 ~ 60	10% ~ 90%

